

## Construction and Inspection

John Zaniewski  
LTAP Consultant  
PO Box 6103  
WVU  
Morgantown, WV 26506

5-1

1

---

---

---

---

---

---

---

## Overview

- Surface Preparation
  - Repairs
  - Clean
  - Tack coat
- Delivery
- Placement
- Compaction
- Inspection

5-2

2

---

---


---

---

---

---

---



3

---

---


---

---

---

---

---



4

---

---

---

---

---

---

---

---



5

---

---

---

---

---

---

---

---



6

---

---

---

---

---

---

---

---



7

---

---

---

---

---

---

---

---



8

---

---

---


---

---

---

---

---



9

---

---

---


---

---

---

---

---



10

---

---

---

---

---

---

---

---



11

---

---

---


---

---

---

---

---



12

---

---

---

---

---

---

---

---

Good patch can  
perform well  
And when overlaid  
provides a good  
foundation for  
pavement performance



13

---

---

---

---

---

---

---

---

Crews test new pothole repair tool



14

---

---

---

---

---

---

---

---

AND....

- Even with good patching practices traffic will densify the patch.
- Best practices
  - Place patches 3 to 6 months prior to overlay.
  - Make all needed corrections to drainage ditches or structures.

S-15

15

---

---

---

---

---

---

---

---



16

---

---

---


---

---

---

---

---



17

---

---

---


---

---

---

---

---



18

---

---

---

---

---

---

---

---

Some surface will show through a properly placed tack coat.

Asphalt emulsions are applied brown, and then turn black after they break (the water separates from the asphalt).

The water from the emulsion must be allowed to evaporate before placing the HMA.

Typical tack coat application rate: 0.04 to 0.06 gal/sq. yd **residual** asphalt.

Too little or too much – both are bad.

19

---

---

---

---

---

---

---

---

Almost every thing done right ☹



5-20

20

---

---

---


---

---

---

---

---



21

---

---

---

---


---

---

---

---

•The center was thinner than the edges—the white aggregate pieces were being crushed by the screed.



WDDOH:  
Types of applications  
Equipment used for placement  
Equipment used for compaction  
Density checked?

22

---

---

---


---

---

---

---

---



Concrete pavement repair

23

---

---

---


---

---

---

---

---



Milling  
Alternative to level up  
Removes distress  
Maintain elevation  
Rough texture – tack coat?

24

---

---

---

---

---

---

---

---



25

---

---

---

---

---

---

---

---



26

---

---

---

---

---

---

---

---



27

---

---

---

---

---

---

---

---

**Bottom (or belly) dump truck**  
Delivers load from beneath, into a windrow  
Capacity: 18 to 23 tons



28

---

---

---

---

---

---

---

---

**Horizontal discharge (live bottom) truck.** Conveyor discharges mix from back, without raising bed, directly into paver. Capacity varies; truck shown has 45 ton payload, used only in Michigan.



29

---

---

---

---

---

---

---

---

**Cover load with tarp while transporting hot mix**



33

---

---

---

---

---

---

---

---

## Four Process for Paving

- Mix production – 200 to 700 tph
- Transportation – balance number of trucks
- Lay down – continuous operation
  - Width of paving
  - Depth of lift
- Compaction – number of rollers

5-34

34

---

---

---

---


---

---

---

---

## Balancing Production



35

---

---

---

---

---

---

---

---

## Number of Trucks Example

Tons scheduled to be placed (MIX): 1800 tons

Hours of paving scheduled (TIME): 10 hours

Rate of mix needed to be delivered to jobsite (H-RATE):

$$= \text{MIX} \div \text{TIME} = 1800 \div 10 = 180 \text{ tph}$$

Rate of mix available from HMA facility (F-RATE): 210 tph

STOP: Is the H-RATE slightly greater than or equal to the F-RATE?

Average Truck Capacity (SIZE): 20 net tons

Total Truck Trips Needed (TRIPS):

$$= \text{MIX} \div \text{SIZE} = 1800 \div 20 = 90 \text{ trips} = \text{TRIPS}$$

5-36

36

---

---

---

---

---

---

---

---

Truck Cycle (in minutes):

Delay at Facility	:	2	:	
Load Time	:		:	2
Ticket & Tarp	:	3	:	
Haul to Job	:		:	19
Delay on site	:	5	:	
Dump/clean up	:	10	:	
Return Haul	:	19	:	

=====

Total cycle in minutes = 60 ÷ 60 min/hr

= Truck Cycle (CYCLE): 1.0 hours/trip

Number of Trips per Truck (LOADS):

= TIME ÷ CYCLE

= 10 ÷ 1.0 = (Round down) 10 trips/truck = LOADS

Number of Trucks Needed (TRUCKS):

= TRIPS ÷ LOADS

= 90 ÷ 10 = (Round up) 9 total trucks = TRUCKS

37

---

---

---

---

---

---


---

---

---

---

Truck Loading Practice



38

---

---

---

---

---


---

---

---

---

---



39

---

---

---

---

---


---

---

---

---

---



40

---

---

---

---

---

---

---

---



41

---

---

---


---

---

---

---

---



42

---

---

---


---

---

---

---

---



43

---

---

---


---

---

---

---

---



44

---

---

---


---

---

---

---

---



45

---

---

---

---

---

---

---

---



46

---

---

---

---

---

---

---

---

Truck hitch and push rollers



48

---

---

---


---

---

---

---

---



49

---

---

---

---

---

---

---

---

### Tracked Paver



50

---

---

---

---

---

---

---

---

The paver hopper is where the mix is received from the truck or pickup machine. The hopper must be wide enough to allow the bed of the truck to fit inside its edges. The hopper must be low enough to allow the truck bed to be raised. Actual purpose of the wings is to reduce the paver width during transport. Folding wings can cause segregation. The wings should be folded while the hopper is relatively full of mix.

**Better never fold the wings and waste the material at the end of the day**



51

---

---

---

---

---

---

---

---

### Slat conveyors

- Slat conveyors at the bottom of the hopper
- Transport the mix from the hopper spreading screws.
- Slat conveyors move independently, to feed each side of the screed.
- Above the slat conveyors at the back wall of the hopper are flow gates.



52

---

---

---

---

---

---

---

---

The augers reside directly between the tractor and screed units, in the auger chamber.

The mix should not cover the augers, nor should the bottom of the augers be visible.

It is important that the head of material is consistent across the screed, to keep forces on the screed constant.



53

---

---

---

---


---

---

---

---

### Material Flow



54

---

---

---

---


---

---

---

---

**Automatic feed control.**  
A sensor measures the head of material and controls the slat conveyors and augers.



55

---

---

---


---

---

---

---

---



58

---

---

---


---

---

---

---

---



59

---

---

---


---

---

---

---

---



60

---

---

---

---

---

---

---

---



61

---

---

---


---

---

---

---

---



64

---

---

---

---

---

---

---

---



67

---

---

---

---


---

---

---

---

## Butt Joint



68

---

---

---


---

---

---

---

## Papered Transverse Joint



69

---

---


---

---

---

---

---



70

---

---


---

---

---

---

---



71

---

---

---

---

---

---

---

---



72

---

---

---


---

---

---

---

---



73

---

---

---


---

---

---

---

---



74

---

---

---


---

---

---

---

---



75

---

---

---

---

---

---

---

---

- To prepare the cold joint for the next mat, clean the joint area, and apply a tack coat if needed.
- Some specs require the joint to be “cut back” 1 to 2 inches before the next mat is placed. This can be done with a saw, or a cutting wheel attached to a grader or loader.
- The purpose of this is to remove the part of the mat that may have less density than the rest of the mat due to lack of confinement during compaction.
- If traffic will not be passing over the mat, cutting back the joint while the mix is still warm requires less effort.
- Cutting back definitely requires a tack coat.

76

---

---

---


---

---

---

---

---



77

---

---

---


---

---

---

---

---



78

---

---

---

---

---

---

---

---



79

---

---

---


---

---

---

---

---



82

---

---

---

---

---

---

---

---