

By Standard Number / 1926.52 - Occupational noise exposure.

---

- **Part Number:** 1926
  - **Part Number Title:** Safety and Health Regulations for Construction
  - **Subpart:** 1926 Subpart D
  - **Subpart Title:** Occupational Health and Environmental Controls
  - **Standard Number:** 1926.52
  - **Title:** Occupational noise exposure.
  - **GPO Source:** e-CFR
- 

#### 1926.52(a)

Protection against the effects of noise exposure shall be provided when the sound levels exceed those shown in Table D-2 of this section when measured on the A-scale of a standard sound level meter at slow response.

#### 1926.52(b)

When employees are subjected to sound levels exceeding those listed in Table D-2 of this section, feasible administrative or engineering controls shall be utilized. If such controls fail to reduce sound levels within the levels of the table, personal protective equipment as required in Subpart E, shall be provided and used to reduce sound levels within the levels of the table.

#### 1926.52(c)

If the variations in noise level involve maxima at intervals of 1 second or less, it is to be considered continuous.

#### 1926.52(d)

-

#### 1926.52(d)(1)

In all cases where the sound levels exceed the values shown herein, a continuing, effective hearing conservation program shall be administered.

TABLE D-2 - PERMISSIBLE NOISE EXPOSURES

Duration per day, hours	Sound level dBA slow response
8.....	90
6.....	92
4.....	95
3.....	97
2.....	100
1 1/2.....	102
1.....	105
1/2.....	110
1/4 or less.....	115

## 1926.52(d)(2)

## 1926.52(d)(2)(i)

When the daily noise exposure is composed of two or more periods of noise exposure of different levels, their combined effect should be considered, rather than the individual effect of each. Exposure to different levels for various periods of time shall be computed according to the formula set forth in paragraph (d)(2)(ii) of this section.

## 1926.52(d)(2)(ii)

$F(e) = (T(1) \text{ divided by } L(1)) + (T(2) \text{ divided by } L(2)) + \dots + (T(n) \text{ divided by } L(n))$  where:

F(e) = The equivalent noise exposure factor.

T = The period of noise exposure at any essentially constant level.

L = The duration of the permissible noise exposure at the constant level (from Table D-2).

If the value of F(e) exceeds unity (1) the exposure exceeds permissible levels.

## 1926.52(d)(2)(iii)

A sample computation showing an application of the formula in paragraph (d)(2)(ii) of this section is as follows. An employee is exposed at these levels for these periods:

110 db A 1/4 hour.

100 db A 1/2 hour.

90 db A 1 1/2 hours.

$$F(e) = (1/4 \text{ divided by } 1/2) + (1/2 \text{ divided by } 2) + (1 \text{ 1/2 divided by } 8)$$
$$F(e) = 0.500 + 0.25 + 0.188$$
$$F(e) = 0.938$$

Since the value of F(e) does not exceed unity, the exposure is within permissible limits.

#### 1926.52(e)

Exposure to impulsive or impact noise should not exceed 140 dB peak sound pressure level.

---

## UNITED STATES DEPARTMENT OF LABOR

Occupational Safety & Health Administration

200 Constitution Ave NW

Washington, DC 20210

☎ 800-321-6742 (OSHA)

TTY

[www.OSHA.gov](http://www.OSHA.gov)

### FEDERAL GOVERNMENT

White House

Severe Storm and Flood Recovery

Assistance

Disaster Recovery Assistance

[DisasterAssistance.gov](http://DisasterAssistance.gov)

[USA.gov](http://USA.gov)

No Fear Act Data

U.S. Office of Special Counsel

### OCCUPATIONAL SAFETY & HEALTH

Frequently Asked  
Questions

A - Z Index

[Freedom of Information Act \(FOIA\)](#)  
[Read The OSHA Newsletter](#)  
[Subscribe to the OSHA Newsletter](#)  
[OSHA Publications](#)  
[Office of Inspector General](#)

## **ABOUT THIS SITE**

[Freedom of Information Act \(FOIA\)](#)  
[Privacy & Security Statement](#)  
[Disclaimers](#)  
[Important Web Site Notices](#)  
[Plug-ins Used by DOL](#)  
[Accessibility Statement](#)